





MISSOURI DEPARTMENT OF HEALTH AND SENIOR SERVICES STATE PUBLIC HEALTH LABORATORY

ALCO-SENSOR IV WITH PRINTER MAINTENANCE REPORT

REPORT #7

STANDARD SUPPLIER GUTH LAB LOT # 9370 EXP. DATE D/91 SIMULATOR TEMPERATURE (34°C ± 0.2°C) 34°C SIMULATOR SN MP 3584 SIMULATOR EXP DATE 0 2/20/000 CALIBRATION CHECK - (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three tests using a standard solution. All three tests must be within ±5% of the standard value and must have a spread of .005 or less. Check the box corresponding to the standard solution being used. (PRINTOUT ATTACHED) 0.100% STANDARD - MUST READ BETWEEN 0.095% and 0.105% INCLUSIVE 0.080% STANDARD - MUST READ BETWEEN 0.076% and 0.084% INCLUSIVE 0.040% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE TEST 1	Complete this report in duplicate at the time Send copy to Department of Health and Se	e of the regular monthly preventative mainten nior Services; retain original in department file	ance check, and whenever instrument is repaired.	
CHECKLIST Place a mark in the bot by each ferm if found to be satisfactory or if operating within established limits. (Write in observed values where determined.) Unmarked items must be corrected before using instrument. DIGITAL READOUT (ALL ELEMENTS OPERATIONAL.) TEMPERATURE OF ALCO SENSOR (10°C - 40°C) PRINTER WORKING PROPERLY TIME AND DATE DISPLAYING PROPERLY BREATH ALCOHOL ACCURACY STANDARDS SIMULATOR SOLUTION			DATE OF INSPECTION	
CHECKLIST Place a mark in the bot by each ferm if found to be satisfactory or if operating within established limits. (Write in observed values where determined.) Unmarked items must be corrected before using instrument. DIGITAL READOUT (ALL ELEMENTS OPERATIONAL.) TEMPERATURE OF ALCO SENSOR (10°C - 40°C) PRINTER WORKING PROPERLY TIME AND DATE DISPLAYING PROPERLY BREATH ALCOHOL ACCURACY STANDARDS SIMULATOR SOLUTION	107985	099.3586.820	6-16-20	
DIGITAL READOUT (ALL ELEMENTS OPERATIONAL) DIGITAL READOUT (ALL ELEMENTS OPERATIONAL) TEMPERATURE OF ALCO SENSOR (10°C - 40°C) PRINTER WORKING PROPERLY TIME AND DATE DISPLAYING PROPERLY BREATH ALCOHOL ACCURACY STANDARDS SIMULATOR SUPPLIER GUTH LAB	LOCATION OF INSTRUMENT (STREET AND CITY)		TIME OF INSPECTION	
DIGITAL READOUT (ALL ELEMENTS OPERATIONAL) DIGITAL READOUT (ALL ELEMENTS OPERATIONAL) TEMPERATURE OF ALCO SENSOR (10°C - 40°C) PRINTER WORKING PROPERLY TIME AND DATE DISPLAYING PROPERLY BREATH ALCOHOL ACCURACY STANDARDS SIMULATOR SUPPLIER GUTH LAB	200 North Are. Sparte	, mo 65755	1235	
DIGITAL READOUT (ALL ELEMENTS OPERATIONAL) TEMPERATURE OF ALCO SENSOR (10°C - 40°C) PRINTER WORKING PROPERLY BREATH ALCOHOL ACCURACY STANDARDS SIMULATOR SOLUTION STANDARD SUPPLIER GUTH LAB LOT # 19370 EXP. DATE 12,1921 SIMULATOR TEMPERATURE (34°C ± 0.2°C) 34°C SIMULATOR SN MP 35°S SMULATOR EXP DATE 02,2000 CALIBRATION CHECK - (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three lests using a standard solution. All three lests must be within ±5% of the standard value and must have a spread of .005 or less. Check the box corresponding to the standard solution being used. (PRINTOUT ATTACHED) 0.100% STANDARD - MUST READ BETWEEN 0.095% and 0.105% INCLUSIVE 0.090% STANDARD - MUST READ BETWEEN 0.095% and 0.04% INCLUSIVE 1.000% STANDARD - MUST READ BETWEEN 0.095% and 0.04% INCLUSIVE 1.000% STANDARD - MUST READ BETWEEN 0.095% and 0.042% INCLUSIVE 1.000% STANDARD - MUST READ BETWEEN 0.095% and 0.042% INCLUSIVE 1.000% STANDARD - MUST READ BETWEEN 0.095% and 0.042% INCLUSIVE 1.000% STANDARD - MUST READ BETWEEN 0.095% and 0.042% INCLUSIVE 1.000% STANDARD - MUST READ BETWEEN 0.095% and 0.042% INCLUSIVE 1.000% STANDARD - MUST READ BETWEEN 0.095% and 0.042% INCLUSIVE 1.000% STANDARD - MUST READ BETWEEN 0.095% and 0.042% INCLUSIVE 1.000% STANDARD - MUST READ BETWEEN 0.095% and 0.042% INCLUSIVE 1.000% STANDARD - MUST READ BETWEEN 0.095% and 0.042% INCLUSIVE 1.000% STANDARD - MUST READ BETWEEN 0.095% and 0.042% INCLUSIVE 1.000% STANDARD - MUST READ BETWEEN 0.095% and 0.042% INCLUSIVE 1.000% STANDARD - MUST READ BETWEEN 0.095% and 0.042% INCLUSIVE 1.000% STANDARD - MUST READ BETWEEN 0.095% and 0.042% INCLUSIVE 1.000% STANDARD - MUST READ BETWEEN 0.095% and 0.105% INCLUSIVE 1.000% STANDARD - MUST READ BETWEEN 0.095% and 0.105% INCLUSIVE 1.000% STANDARD - MUST READ BETWEEN 0.095% and 0.105% INCLUSIVE 1.000% STANDARD - MUST READ BETWEEN 0.095% and 0.105% INCLUSIVE 1.000% STANDARD - MUST READ BETWEEN 0.095% and 0.105% INCLUSIVE 1.000% STANDARD - MUST READ BETWEEN 0.095% and 0.105% INCLUSIVE	CHECKLIST: Place a mark in the box by each item if found to be satisfactory or if operating within established limits. (Write in observed val-			
TEMPERATURE OF ALCO SENSOR (10°C - 40°C) PRINTER WORKING PROPERLY TIME AND DATE DISPLAYING PROPERLY BREATH ALCOHOL ACCURACY STANDARDS SIMULATOR SOLUTION		ust be corrected before using instrument.		
PRINTER WORKING PROPERLY TIME AND DATE DISPLAYING PROPERLY				
TIME AND DATE DISPLAYING PROPERLY BREATH ALCOHOL ACCURACY STANDARDS SIMULATOR SOLUTION COMPRESSED ETHANOL-GAS MIXTURE STANDARD SUPPLIER GUTH LAB LOT # 19370 EXP. DATE 12/92/1 SIMULATOR TEMPERATURE (34°C ± 0.2°C) 34°C SIMULATOR SN MP 3584 SIMULATOR EXP DATE 02/30/200 CALIBRATION CHECK - (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three tests using a standard solution. All three tests must be within ±5% of the standard value and must have a spread of .005 or less. Check the box corresponding to the standard solution being used. (PRINTOUTA TITACHED) 10.100% STANDARD - MUST READ BETWEEN 0.095% and 0.105% INCLUSIVE 0.100% STANDARD - MUST READ BETWEEN 0.095% and 0.042% INCLUSIVE 0.040% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE TEST 1 * 10 2 TEST 2 * . (0 3 TEST 3 * . 10 2 TEST 1 * 10 2 TEST 2 * . (0 3 TEST 3 * . 10 2 TEST 1 * 10 2 TEST 2 * . (0 3 TEST 3 * . 10 2 TEST 1 * 10 2 TEST 2 * . (0 3 TEST 3 * . 10 2 TEST 1 * 10 2 TEST 2 * . (0 3 TEST 3 * . 10 2 TEST 1 * 10 2 TEST 2 * . (0 3 TEST 3 * . 10 2 TEST 1 * 10 2 TEST 2 * . (0 3 TEST 3 * . 10 2 TEST 1 * 10 2 TEST 2 * . (0 3 TEST 3 * . 10 2 TEST 1 * 10 2 TEST 2 * . (0 3 TEST 3 * . 10 2 TEST 1 * 10 2 TEST 2 * . (0 3 TEST 3 * . 10 2 TEST 1 * 10 2 TEST 2 * . (0 3 TEST 3 * . 10 2 TEST 1 * 10 2 TEST 2 * . (0 3 TEST 3 * . 10 2 TEST 1 * 10 2 TEST 2 * . (0 3 TEST 3 * . 10 2 TEST 3 * . (0 3 TES	TEMPERATURE OF ALCO SENSOR (10°C - 40°C)			
SIMULATOR SOLUTION COMPRESSED ETHANOL-GAS MIXTURE SIMULATOR SUPPLIER GUTH LAB LOT # 19.370 EXP. DATE DJ 9/21 SIMULATOR TEMPERATURE (34°C ± 0.2°C) 34°C SIMULATOR SN MP 3584 SIMULATOR EXP DATE 02/20/20/20 CALIBRATION CHECK - (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three tests using a standard solution. All three tests must be within ±5% of the standard value and must have a spread of .005 or less. Check the box corresponding to the standard solution being used. (PRINTOUT ATTACHED) 0.080% STANDARD - MUST READ BETWEEN 0.095% and 0.0105% INCLUSIVE 0.080% STANDARD - MUST READ BETWEEN 0.095% and 0.084% INCLUSIVE TEST 1 *				
SIMULATOR SOLUTION COMPRESSED ETHANOL-GAS MIXTURE STANDARD SUPPLIER GUTH LAB LOT # 19.3.70 EXP. DATE 12/9.4 SIMULATOR TEMPERATURE (34°C ± 0.2°C) 3.4°C SIMULATOR SN MP 35.84 SIMULATOR EXP DATE 0.2/20/062 CALIBRATION CHECK - (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three tests using a standard solution. All three tests must be within ±5% of the standard value and must have a spread of .005 or less. Check the box corresponding to the standard solution being used. (PRINTOUT ATTACHED) 0.100% STANDARD - MUST READ BETWEEN 0.095% and 0.105% INCLUSIVE 0.080% STANDARD - MUST READ BETWEEN 0.036% and 0.042% INCLUSIVE 1.000% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIV	TIME AND DATE DISPLAYING PROPERLY			
STANDARD SUPPLIER GUTH LAB LOT # 9370 EXP. DATE 12/91 SIMULATOR TEMPERATURE (34°C ± 0.2°C) 34°C SIMULATOR SN MP 3584 SIMULATOR EXP DATE 0 2/20/200 CALIBRATION CHECK - (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three tests using a standard solution. All three tests must be within ±5% of the standard value and must have a spread of .005 or less. Check the box corresponding to the standard solution being used. (PRINTOUT ATTACHED) 0.100% STANDARD - MUST READ BETWEEN 0.095% and 0.105% INCLUSIVE 0.080% STANDARD - MUST READ BETWEEN 0.076% and 0.084% INCLUSIVE 1.00/200% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE 1.00/200% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE 1.00/200% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE 1.00/200% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE 1.00/200% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE 1.00/200% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE 1.00/200% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE 1.00/200% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE 1.00/200% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE 1.00/200% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE 1.00/200% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE 1.00/200% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE 1.00/200% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE 1.00/200% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE 1.00/200% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE 1.00/200% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE 1.00/200% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE 1.00/200% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE 1.00/200% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE 1.00/200% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE 1.00/200% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE 1.00/200% STANDARD - MUST READ BETWEEN 0.038% and 0.042% I	BREATH ALCOHOL ACCURACY STANDA	ARDS		
SIMULATOR TEMPERATURE (34°C ± 0.2°C) 34°C SIMULATOR SN MP 3584 SIMULATOR EXP DATE 02/20/2005 SIMULATOR SN MP 3584 SIMULATOR EXP DATE 02/20/2005 SIMULATOR SN MP 3584 SIMULATOR EXP DATE 02/20/2005 SIMULATOR EXP DATE 02	SIMULATOR SOLUTION	☐ COMPRESSE	D ETHANOL-GAS MIXTURE	
SIMULATOR TEMPERATURE (34°C ± 0.2°C) 34°C SIMULATOR SN MP 3589 SIMULATOR EXP DATE 0 2/30/ptg CALIBRATION CHECK — (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three tests using a standard solution. All three tests must be within ±5% of the standard value and must have a spread of .005 or less. Check the box corresponding to the standard solution being used. (PRINTOUT ATTACHED) 0.100% STANDARD - MUST READ BETWEEN 0.055% and 0.105% INCLUSIVE 0.040% STANDARD - MUST READ BETWEEN 0.076% and 0.042% INCLUSIVE 1.000% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE TEST 1			EXP. DATE	
Hun three tests using a standard solution. All three tests must be within ±5% of the standard value and must have a spread of .005 or less. Check the box corresponding to the standard solution being used. (PRINTOUT ATTACHED) 0.100% STANDARD - MUST READ BETWEEN 0.095% and 0.105% INCLUSIVE 0.080% STANDARD - MUST READ BETWEEN 0.076% and 0.084% INCLUSIVE 0.040% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE 1.02	SIMULATOR TEMPERATURE (34°C ± 0.2°C) 34°C SIMULATOR SN MP 3584 SIMULATOR EXP DATE 02/20/2005			
RFI DETECTOR OPERATING INDICATE THE NUMBER OF BREATH TESTS IN THE FOLLOWING RANGES SINCE THE LAST MAINTENANCE REPORT: (DO NOT INCLUDE SELF-ADMINISTERED TESTS) REFUSALS (004) (.0509) (.1014) (.1519) (OVER .19) List any new parts and describe any alteration or modification that was made to restore the instrument to operate satisfactorily and within established limits (use other side if necessary). NEW PRINT NAME LOKEN WYSTERM TYPE ILDERMIT NUMBER ALORE	Hun three tests using a standard solution. All three tests must be within ±5% of the standard value and must have a spread of .005 or less. Check the box corresponding to the standard solution being used. (PRINTOUT ATTACHED) 0.100% STANDARD - MUST READ BETWEEN 0.095% and 0.105% INCLUSIVE 0.080% STANDARD - MUST READ BETWEEN 0.076% and 0.084% INCLUSIVE			
INDICATE THE NUMBER OF BREATH TESTS IN THE FOLLOWING RANGES SINCE THE LAST MAINTENANCE REPORT: (DO NOT INCLUDE SELF-ADMINISTERED TESTS) REFUSALS (004) (0509) (.1014) (.1519) (OVER .19) List any new parts and describe any alteration or modification that was made to restore the instrument to operate satisfactorily and within established limits (use other side if necessary). INSPECTING OFFICER SIGNATURE TYPE I DEMMIT NUMBER/JEXAMATION DATE 20056 3/1/2021 TELEPHONE NUMBER 417-242-55((TEST 1 € .102	TEST 2 - 103	TEST 3 ♥ .(0 ⊃	
REFUSALS (004) (.0509) (.1014) (.1519) (OVER .19) 1 List any new parts and describe any alteration or modification that was made to restore the instrument to operate satisfactorily and within established limits (use other side if necessary). New ridge INSPECTING OFFICER SIGNATURE TYPE ILLEPHONE NUMBER 210056 3 / 1/302 i TELEPHONE NUMBER 417 - 242-55 ((RFI DETECTOR OPERATING			
INSPECTING OFFICER SIGNATURE SIGNATURE TYPE ILLERMINIT NUMBERIEXIPHRATION DATE 20056 (004) (.0509) (.1014) (.1519) (.1519) (.1519) (.1519) (.1519) (.1519) (.1519) (.1519) (.1519) (.1519) (OVER .19) (OVER .19) (IIII) (IIIII) (IIII) (IIII) (IIIII) (IIII) (IIIIIIII	INDICATE THE NUMBER OF BREATH TESTS IN THE FOLLOWING RANGES SINCE THE LAST MAINTENANCE REPORT: (DO NOT INCLUDE SELF-ADMINISTERED TESTS)			
INSPECTING OFFICER SIGNATURE TYPE ILLERMITI NUMBER/EXMIRATION DATE 290056 (0.0509) (.1014) (.1519) (.1519) (OVER.19) (.1519) (OVER.19) (OVER.19) (I.1014) (.1519) (I.1014) (IIII) (IIII) (IIII) (IIIII) (IIIIIIII	α α		T i	
List any new parts and describe any alteration or modification that was made to restore the instrument to operate satisfactorily and within established limits (use other side if necessary). NSPECTING OFFICER PRINT NAME			-0/	
SIGNATURE PRINT NAME LOKEN NYSTROW TYPE II DEFINIT NUMBER/EXPIRATION DATE TELEPHONE NUMBER 417-242-55 ((List any new parts and describe any alteration or modification that was made to restore the instrument to operate satisfactorily and within			
SIGNATURE PRINT NAME LOKEN NYSTROW TYPE II DEFINIT NUMBER/EXPIRATION DATE TELEPHONE NUMBER 417-242-55 ((
SIGNATURE PRINT NAME LOKEN NYSTROW TYPE II DEFINIT NUMBER/EXPIRATION DATE TELEPHONE NUMBER 417-242-55 ((-			
SIGNATURE PRINT NAME LOKEN NYSTROW TYPE II DEFINIT NUMBER/EXPIRATION DATE TELEPHONE NUMBER 417-242-55 ((
SIGNATURE PRINT NAME LOKEN NYSTROW TYPE II DEFINIT NUMBER/EXPIRATION DATE TELEPHONE NUMBER 417-242-55 ((
SIGNATURE PRINT NAME LOKEN NYSTROW TYPE II DEFINIT NUMBER/EXPIRATION DATE TELEPHONE NUMBER 417-242-55 ((
SIGNATURE PRINT NAME LOKEN NYSTROW TYPE II DEFINIT NUMBER/EXPIRATION DATE TELEPHONE NUMBER 417-242-55 ((INCREATING OFFICER		-	
TYPE IL DEFINIT NUMBER/EXPIRATION DATE LOREN NUMBER TELEPHONE NUMBER 417-242-55 ((自由各种的自己。在中的大型类型的基础的基础的	· 1000 ·	
290056 3/1/2021 TELEPHONE NUMBER 417-242-55((· //(A			
290056 3/1/2021 417-242-55(1	TYPE IL DEAMIT NUMBER/EXPIRATION DATE		TELEPHONE NUMBER	
		~ / /	The second of the second control of the seco	
neturn completed report to the: Breath Alcohol Program, MO Department of Health and Senior Services, Southeast District Office	V	Alcohol Program, MO Department of Health ar		
Return completed report to the: Breath Alcohol Program, MO Department of Health and Senior Services, Southeast District Office 2875 James Boulevard Poplar Bluff, MO 63901	2875 Ja	imes Boulevard	Common Convictors, Countried St. District Office	

AS IV Serial no: 107985
Version no: 532B

TEST RECORD 00912
9/
Temp Date Time 210L
Air Blank: 06/16/20 11:38 .000
Calibration Check: 22 06/16/20 11:38 .103

Subject Name

Test
Subject I.D.

Joren Lystrous
Location
Sparta PD ROOKing

AS IV Serial no: 107985
Version no: 532B

TEST RECORD 00913

9/
Temp Date Time 210L

Air Blank:
06/16/20 11:41 .000
Calibration Check:
22 06/16/20 11:41 .102

Subject Name
(eSt
Subject I.D.

3
Operator Name, I.D.

Location

Sarta R. A. Rooking

AS IV Serial no: 107985
Version no: 532B

TEST RECORD 00914

S/
Temp Date Time 210L

VOID: RFI
12 06/16/20 11:43

Subject Name

Test
Subject I.D.

Coerator Name, I.D.

Location

Spata P.D. GOOK....

TEST RECORD 00915

TEST RECORD 00915

Solution Pate Time 210L

Air Blank: 06/16/20 11:45.000

Calibration Check: 22 06/16/20 11:45.000

Subject Name

Test

Subject I.D.

Blank

Operator Name, I.D.

L.Mitrom 6(5)

Location

AS IV Serial no: 107985



STATE OF MISSOURI

DEPARTMENT OF HEALTH AND SENIOR SERVICES
BREATH ALCOHOL PROGRAM



PERMIT TYPE II

LOREN NYSTROM

is hereby authorized to instruct and supervise operators, train instructors, inspect, calibrate, perform field service and repairs, and operate the following breath analyzer(s):

ALCO-SENSOR IV WITH PRINTER

for the determination of the alcoholic content of blood from a sample of expired air. Permit issued under the provisions of sections 577.020 through 577.041, RSMo and 306.111 through 306.119 RSMo.

DATE	want
NUMBER 290056	DIRECTOR OF STATE PUBLIC HEALTH LABORATORY
EXPIRES 3/1/2021	- fill dille
RO 553-0771 (5-10)	DIRECTOR OF DEPARTMENT OF HEALTH AND SENIOR SERVICES
	LAB-4 (R6-10)



STATE OF MISSOURI DEPARTMENT OF HEALTH AND SENIOR SERVICES BREATH ALCOHOL PROGRAM

INSTRUMENT OPERATOR CARD

The named cardholder is authorized to operate an evidential breath alcohol instrument for the determination of the alcoholo content in breath form of expired all in Missouri.

Operator NYSTROM, LOREN

Permit No 290056 Date Issued 3/1/2019

19 Date Expires 3/1/2021

